

ALTEA



7131/01




7131/03



7131/04




7131/06



7131/07



7131/08



7131/10




7131/11




7131/12



7131/16




7131/17




7131/18



7131/26




7131/27




7131/28



7131/37



7131/44



Ref.	cm	g/m ²						Price category	Appearance
7131/01	320	88	80% PL 20% LI	Yes				B	plain
7131/03	320	88	80% PL 20% LI	Yes				B	plain
7131/04	320	88	80% PL 20% LI	Yes				B	plain
7131/06	320	88	80% PL 20% LI	Yes				B	plain
7131/07	320	88	80% PL 20% LI	Yes				B	plain
7131/08	320	88	80% PL 20% LI	Yes				B	plain
7131/10	320	88	80% PL 20% LI	Yes				B	plain
7131/11	320	88	80% PL 20% LI	Yes				B	plain
7131/12	320	88	80% PL 20% LI	Yes				B	plain

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded



Weight



Composition









Upholstery



Selvedge

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, CAN BE DRY CLEANED, DRIP DRY, SHRINKAGE AFTER FIRST WASH 0-2% FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.

Ref.	 cm	 g/m ²					Price category	Appearance
7131/16	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/17	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/18	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/26	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/27	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/28	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/37	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain
7131/44	320	88	80% PL 20% LI	Yes	Vertical ceiling/floor	Sheer	B	plain

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded



Weight



Composition



Upholstery



Selvedge

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, CAN BE DRY CLEANED, DRIP DRY, SHRINKAGE AFTER FIRST WASH 0-2% FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.