

Astra F.R. Plì 20mm




TP/AST/01




TP/AST/02



TP/AST/03



TP/AST/04




TP/AST/05




TP/AST/06




TP/AST/07




TP/AST/08



TP/AST/09



TP/AST/13




TP/AST/16



TP/AST/20




TP/AST/22




TP/AST/26




TP/AST/35




TP/AST/36



TP/AST/37



TP/AST/38



Name	Cat.	Ref.																									
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02			

Astra F.R. Plì 20mm	ASTp	TP/AST/01	100% PL Trevira CS	Classe1 (I), M1 (F), B1 (D), BS (GB), EN 13773 Class 1 (EU)	OEKO-TEX REACH	230	170	0,35			43	50	7	45	54	0,41						90			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/02	100% PL Trevira CS			230	170	0,35			32	48	20	42	55	0,42						89			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/03	100% PL Trevira CS			230	170	0,35			40	47	13	37	46	0,42						83			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/04	100% PL Trevira CS			230	170	0,35			28	37	35	17	39	0,45						83			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/05	100% PL Trevira CS			230	170	0,35			36	49	15	31	46	0,42						85			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/06	100% PL Trevira CS			230	170	0,35			32	42	26	20	30	0,44						86			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/07	100% PL Trevira CS			230	170	0,35			12	13	75	13	16	0,53						81			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/08	100% PL Trevira CS			230	170	0,35			13	7	80	11	5	0,55						81			6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/09	100% PL Trevira CS			230	170	0,35			20	52	28	30	55	0,40						86			6/7		

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another


Width


Composition


Health certification


IMO - Fabrics for marine industry


Solar reflection


Light absorption


Sound absorption


Thickness


Flame retardant


Colour fastness


Openess factor


Solar absorption


G tot Type C - GLASS


Warp - Weft N5 cm


Weight


Transparency


Sealable


Solar transmission


Light transmission


UV reduction


Glare control

MAINTENANCE DO NOT USE WATER: INTERVENE USING DRY METHODS FOR REMOVING DUST DEPOSITS.

Name	Cat.	Ref.																									
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02			

Astra F.R. Plì 20mm	ASTp	TP/AST/13	100% PL Trevira CS	Classe1 (I), M1 (F), B1 (D), BS (GB), EN 13773 Class 1 (EU)	OEKO-TEX REACH	230	170	0,35			21	28	51	18	36	0,48					87				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/16	100% PL Trevira CS			230	170	0,35			12	16	72	13	17	0,52					82				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/20	100% PL Trevira CS			230	170	0,35			13	30	57	14	32	0,47					85				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/22	100% PL Trevira CS			230	170	0,35			34	39	27	22	26	0,45					81				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/26	100% PL Trevira CS			230	170	0,35			28	49	23	32	53	0,41					87				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/35	100% PL Trevira CS			230	170	0,35			16	33	51	14	36	0,46					80				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/36	100% PL Trevira CS			230	170	0,35			25	50	25	31	57	0,41					87				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/37	100% PL Trevira CS			230	170	0,35			37	43	20	25	31	0,44					77				6/7		
Astra F.R. Plì 20mm	ASTp	TP/AST/38	100% PL Trevira CS			230	170	0,35			23	51	26	30	57	0,41					84				6/7		

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another


Width


Composition


Health certification


IMO - Fabrics for marine industry


Solar reflection


Light absorption


Sound absorption


Thickness


Flame retardant


Colour fastness


Openess factor


Solar absorption


G tot Type C - GLASS


Warp - Weft N5 cm


Weight


Transparency


Sealable


Solar transmission


Light transmission


UV reduction


Glare control

MAINTENANCE DO NOT USE WATER: INTERVENE USING DRY METHODS FOR REMOVING DUST DEPOSITS.