

BLUSCREEN







Ref. WARP

BLUS/01	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	27	64	9	28	0,36	0,18	90	115	115
BLUS/02	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	21	56	23	19	0,39	0,15	90	115	115
BLUS/03	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	13	43	44	9	0,43	0,11	100	115	115
BLUS/04	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	15	48	37	14	0,41	0,12	95	115	115
BLUS/05	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	5	32	63	4	0,45	0,07	100	115	115
BLUS/06	320	0,60	290	100% SOLUTION DYED ACRYLIC	Dimout	CLEANGUARD OUTDOOR TREATMENT, OEKO-TEX, WATER	7/8	No	No	1	14	85	1	0,51	0,05	100	115	115

All coefficients have a possible tolerance of +/- 5% Attention: colour shades may vary slightly from one dye lot to another



Width





Health certification



IMO - Fabrics for marine industry



Solar reflection



Light absorption



Sound absorption



Thickness



Flame retardant



Colour fastness



Openess factor



Solar absorption



G tot Type C -GLASS



Warp - Weft N5 cm



Weight



Transparency



Sealable



Solar transmission



Light transmission



UV reduction

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS, DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC, WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS, REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY, RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.