



Cosmo F.R.- 4 pass Flock - Blackout




7124/01




7124/02




7124/03




7124/04




7124/05




7124/06




7124/07




7124/08










7124/09



7124/10



Ref.	 cm	 g/m ²						Price category	Appearance
7124/01	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	C	plain
7124/02	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	C	plain
7124/03	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	C	plain
7124/04	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/05	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/06	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/07	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/08	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/09	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain
7124/10	280	400	100% PL (acrylic back coating)	Class 1(I),EN 13773 (EU), IMO MED 2014/90/EU B TYPE	No	Vertical ceiling/floor	Blackout	D	plain

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye-lot to another



TESSUTI & SARTORIA



Width



Weight



Flame retardant



Composition



Transparency



Upholstery



Leaded



Selvedge

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, DO NOT DRY CLEAN, DRIP DRY. SHRINKAGE AFTER FIRST WASH 0-2%. FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.