




# *Cristal KS 50 F.R.*
























**KS/50-140**



Name	Cat.	Ref.	Composition	F.R. classification	Health certifications	Width cm	Weight g/m2	Thickness mm	OF %	Shading	TS %	RS %	AS %	TL %	RL %	INT Type C glass	EXT Type C glass	INT Type D glass	EXT Type D glass	Glare control	↓UV %	αω	Mechanical resistance WARP daN/5cm	Mechanical resistance WEFT daN/5cm	Colour fastness to light	OUTDOOR	Sealable	
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02		
<b>Cristal KS 50 F.R.</b>	KS	KS/50-140	100% PVC	Classe 1(I), M2(F), Cs3d0 (EU)	 RECYCLABLE	140	610	0,50			85	8	7	89	8		0,57										✓	heat

All coefficients have a possible tolerance of +/- 5%  
 Attention: colour shades may vary slightly from one dye lot to another

	Width		Composition		Health certification		IMO - Fabrics for marine industry		Solar reflection		Light absorption		Sound absorption
	Thickness		Flame retardant		Colour fastness		Openess factor		Solar absorption		G tot Type C - GLASS		Warp - Weft N5 cm
	Weight		Transparency		Sealable		Solar transmission		Light transmission		UV reduction		Glare control

**MAINTENANCE** TO REMOVE DIRT AND DUST, WE RECOMMEND THE USE OF THE CLEANING PRODUCT APCO CRISTAL PLUS, FOLLOWED BY APCO CRISTALPLUS LUBRILUX AFTER WASHING. THE USE OF WATER IS ALLOWED, BUT ONLY USA A GENTLE SETTING ON A PRESSURE WASHER. ALLOW TO DRY BEFORE ROLLING UP OR FOLDING.