

Galata F.R.




GAL/01



GAL/02



GAL/03



| Name | Cat. | Ref. | Composition | F.R. classification | Health certifications | Width cm | Weight g/m ² | Thickness mm | OF % | Shading | TS % | RS % | AS % | TL % | RL % | INT Type C glass | EXT Type C glass | INT Type D glass | EXT Type D glass | Glare control | ↓UV % | αw | Mechanical resistance WARP daN/5cm | Mechanical resistance WEFT daN/5cm | Colour fastness to light | OUTDOOR | Sealable |
|--------------------|------|------|-------------|---------------------|-----------------------|----------|-------------------------|-------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|------------------|------------------|------------------|------------------|---------------|--------------|--------------|------------------------------------|------------------------------------|--------------------------|---------|----------|
| Reference Standard | | | | | | | UNI EN ISO 2286-2 | UNI EN ISO 2286-3 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | UNI EN 14501 | EN ISO 11654 | UNI EN ISO 1421 | UNI EN ISO 1421 | UNI EN ISO 105 B02 | | |

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------|-----|--------|---------------------|-------------------------------------|-------------------|-----|-----|------|---|---|----|----|----|----|----|------|--|--|--|--|---|----|--|--|---|--------------------------------|
| Galata F.R. | GAL | GAL/01 | 100% PL FR Recycled | Classe 1 (I), EN 13773 Class 1 (EU) | OEKO-TEX RECYCLED | 320 | 240 | 0,55 | 2 | ○ | 20 | 55 | 25 | 17 | 54 | 0,39 | | | | | 1 | 95 | | | 5 | with tape using high frequency |
| Galata F.R. | GAL | GAL/02 | 100% PL FR Recycled | | | 320 | 240 | 0,55 | 2 | ○ | 19 | 53 | 28 | 17 | 53 | 0,40 | | | | | 1 | 95 | | | 5 | |
| Galata F.R. | GAL | GAL/03 | 100% PL FR Recycled | | | 320 | 240 | 0,55 | 2 | ○ | 13 | 43 | 44 | 12 | 42 | 0,43 | | | | | 2 | 96 | | | 5 | |

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye lot to another

| | | | | | | | | | | | | | |
|--|-----------|--|-----------------|--|----------------------|--|-----------------------------------|--|--------------------|--|----------------------|--|-------------------|
| | Width | | Composition | | Health certification | | IMO - Fabrics for marine industry | | Solar reflection | | Light absorption | | Sound absorption |
| | Thickness | | Flame retardant | | Colour fastness | | Openess factor | | Solar absorption | | G tot Type C - GLASS | | Warp - Weft N5 cm |
| | Weight | | Transparency | | Sealable | | Solar transmission | | Light transmission | | UV reduction | | Glare control |

MAINTENANCE REMOVE THE BLIND FROM THE SYSTEM, ROLL NO FOLDING. SOAK IN WARM WATER MAX 30° WITH DELICATE DETERGENT. MARKS AND DUST CAN BE REMOVED WITH A SOFT BRUSH (DO NOT BEND OR WRING). RINSE CLOTH THOUROUGHLY WITH WATER AND DRAIN (DO NOT WRING OR FOLD). HANG THE FABRIC WHILE DAMP AND LEAVE TO DRY. CAN BE IRONED AT SETTING 1.