


INSECT SCREEN F.R. H.305



IS/BLACK-305



Ref.	cm	mm	g/m ²															
																EXT	WARP	WEFT
IS/BLACK-305	305	0,51	200	35% PL 65% PVC	Classe1 (I), BS(GB), NFPA 701 (US)	Transparent	REACH	heat	No	50.00	44	2	54	44	2	0,34	110	85

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another

Width	Composition	Health certification	IMO - Fabrics for marine industry	Solar reflection	Light absorption
Thickness	Flame retardant	Colour fastness	Openness factor	Solar absorption	G tot Type C - GLASS
Weight	Transparency	Sealable	Solar transmission	Light transmission	Sound absorption
				UV reduction	Warp - Weft N5 cm

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.