



LINO COEX F.R.



7103/01



7103/02










7103/03



7103/04



Ref.	 cm	 g/m ²						Categoria Prezzo	Aspetto
7103/01	330	119	100% LI	Class 1(I), M1 (F), B1&B2(D)	No	Verticale - soffitto/ pavimento	Filtrante	E	Unito
7103/02	330	119	100% LI	Class 1(I), M1 (F), B1&B2(D)	No	Verticale - soffitto/ pavimento	Filtrante	E	Unito
7103/03	330	119	100% LI	Class 1(I), M1 (F), B1&B2(D)	No	Verticale - soffitto/ pavimento	Filtrante	E	Unito
7103/04	330	119	100% LI	Class 1(I), M1 (F), B1&B2(D)	No	Verticale - soffitto/ pavimento	Filtrante	E	Unito

Tutti i coefficienti potrebbero avere una tolleranza di +/- 5%
 Attenzione: La tonalità dei colori può variare leggermente da lotto a lotto



Larghezza



Ignifugo



Trasparenza



Piombato



Peso



Composizione



Imbottito



Cimosa

MANUTENZIONE

LAVARE IN ACQUA A 30°MAX, NO CANDEGGIO, NO TAMBURO, FERRO A 2, SÌ A LAVAGGIO A SECCO, STENDERE APPESO. RITIRO AL PRIMO LAVAGGIO 3-5%. AGGIUNGERE SOLFATO AMMONIO INVECE CHE AMMORBIDENTE. DATI SPECIFICI SU SCHEDA PRODOTTO INDIVIDUALE IN ATELIER