


Movie Ombreg. Liscio R3




R3/331






















R3/338




R3/340




Name	Cat.	Ref.																									
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02			

Movie R3	R3	R3/331	100% PET			152	106	0,08			84	8	8	86	14						99						
Movie R3	R3	R3/338	100% PET			182	106	0,08			16	22	62	7	26						100						with tape using high frequency
Movie R3	R3	R3/340	100% PET			152	102	0,08			3	68	29	2	67						100						


All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye lot to another




Width




Composition




Health certification




IMO - Fabrics for marine industry




Solar reflection




Light absorption




Sound absorption




Thickness




Flame retardant




Colour fastness




Openess factor




Solar absorption




G tot Type C - GLASS




Warp - Weft N5 cm




Weight




Transparency




Sealable




Solar transmission



Light transmission



UV reduction



Glare control

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.