

Screen G2 F.R.




G/279-320



G/281-320




G/282-320



G/286-320




G/290-285



G/291-320



G/292-320




G/293-320



G/294-320




G/295-320



G/296-320



G/297-320



Name	Cat.	Ref.	 Composition	 F.R. classification	 Health certifications	 Width cm	 Weight g/m2	 Thickness mm	 OF %	 Shading	 TS %	 RS %	 AS %	 TL %	 RL %	 INT Type C glass	 EXT Type C glass	 INT Type D glass	 EXT Type D glass	 Glare control	↓UV %	αw	Mechanical resistance WARP daN/5cm	Mechanical resistance WEFT daN/5cm	Colour fastness to light	OUTDOOR	Sealable
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02		

Screen G2 F.R.	G2	G/279-320	42% FV 58% PVC	Euroclass C-s3-d0(EU), Classe 1 (I), M1(F),B1(D), BS(GB),NFPA 701 (US), EN 13773 Classe 1(ES)	 ANTIBACTERIAL GREENGUARD GOLD REACH	320	520	0,75	4		11	27	62	9	27	0,48	0,08		0,06	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/281-320	42% FV 58% PVC			320	520	0,75	4		5	12	83	5	11	0,54	0,06		0,05	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/282-320	42% FV 58% PVC			320	520	0,75	4		16	45	39	14	48	0,40	0,12		0,07	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/286-320	42% FV 58% PVC			320	520	0,75	4		10	28	62	8	27	0,48	0,08		0,06	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/290-285	42% FV 58% PVC			285	520	0,75	4		5	17	78	5	17	0,52	0,06		0,05	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/291-320	42% FV 58% PVC			320	520	0,75	4		4	6	90	4	6	0,56	0,05		0,04	3	96		220	200	7/8	✓	heat

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another



Width



Composition



Health certification



IMO - Fabrics for marine industry



Solar reflection



Light absorption



Sound absorption



Thickness



Flame retardant



Colour fastness



Openess factor



Solar absorption



G tot Type C - GLASS



Warp - Weft N5 cm



Weight



Transparency



Sealable



Solar transmission



Light transmission



UV reduction



Glare control

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.

Name	Cat.	Ref.																									
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02			

Screen G2 F.R.	G2	G/292-320	42% FV 58% PVC	Euroclass C-s3-d0(EU), Classe 1 (I), M1(F),B1(D), BS(GB),NFPA 701 (US), EN 13773 Classe 1(ES)	 ANTIBACTERIAL GREENGUARD GOLD REACH	320	520	0,75	4		14	38	48	13	40	0,42	0,11		0,07	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/293-320	42% FV 58% PVC			320	520	0,75	4		8	20	72	7	17	0,51	0,07		0,05	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/294-320	42% FV 58% PVC			320	520	0,75	4		10	31	59	7	31	0,47	0,08		0,05	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/295-320	42% FV 58% PVC			320	520	0,75	4		17	50	33	16	55	0,37	0,12		0,08	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/296-320	42% FV 58% PVC			320	520	0,75	4		21	66	13	21	73	0,31	0,16		0,09	3	96		220	200	7/8	✓	heat
Screen G2 F.R.	G2	G/297-320	42% FV 58% PVC			320	520	0,75	4		18	53	29	16	58	0,37	0,13		0,08	3	96		220	200	7/8	✓	heat

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another



Width



Composition



Health certification



IMO - Fabrics for marine industry



Solar reflection



Light absorption



Sound absorption



Thickness



Flame retardant



Colour fastness



Openess factor



Solar absorption



G tot Type C - GLASS



Warp - Weft N5 cm



Weight



Transparency



Sealable



Solar transmission



Light transmission



UV reduction



Glare control

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.