


Sogno F.R.




7134/01




7134/02




7134/03



7134/04




7134/05




7134/06



7134/07



7134/08



7134/09




7134/10



7134/11



7134/12




7134/14



7134/15




7134/16




Sogno F.R.




7134/17




7134/18










7134/19



7134/20



Ref.	 cm	 g/m ²						Price category	Appearance
7134/01	310	292	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/02	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/03	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/04	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/05	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/06	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/07	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/08	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/09	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded



Weight



Composition










Upholstery



Selvage

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, DO NOT DRY CLEAN, DRIP DRY. SHRINKAGE AFTER FIRST WASH 0-2%. FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.

Ref.	 cm	 g/m ²						Price category	Appearance
7134/10	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/11	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/12	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/14	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/15	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/16	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/17	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/18	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain
7134/19	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded



Weight



Composition



Upholstery



Selvage

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, DO NOT DRY CLEAN, DRIP DRY. SHRINKAGE AFTER FIRST WASH 0-2%. FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.

Ref.	 cm	 g/m ²						Price category	Appearance
7134/20	310	287	100% PL FR	Class 1(I), B1&B2(D),EN 13773 (EU)	No	Vertical ceiling/floor	Blackout	C	plain

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded




Weight



Composition



Upholstery



Selvedge

MAINTENANCE
WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, DO NOT DRY CLEAN, DRIP DRY. SHRINKAGE AFTER FIRST WASH 0-2%. FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.