



Soltis 92 F.R.




S92/211



S92/213




S92/214




S92/216




S92/221




S92/222




S92/223




S92/224




S92/225




S92/226




S92/227



S92/228



S92/229



Name	Cat.	Ref.	 Composition	 F.R. classification	 Health certifications	 Width cm	 Weight g/m2	 Thickness mm	 OF %	 Shading	 TS %	 RS %	 AS %	 TL %	 RL %	 INT Type C glass	 EXT Type C glass	 INT Type D glass	 EXT Type D glass	 Glare control	↓UV %	αw	Mechanical resistance WARP daN/5cm	Mechanical resistance WEFT daN/5cm	Colour fastness to light	OUTDOOR	Sealable
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02		

Soltis 92 F.R.	S92	S92/211	40% PL 60% PVC	Euroclass B-s2,d0 (EU) Classe 1 (I), M1 (F), B1 (D), BS (GB), NFPA 701 (US), G1 (RU), VKF (CH), IMO	GREENGUARD GOLD  RECYCLABLE	267	420	0,45	4		19	68	13	17		0,24	0,15	0,11	0,07				310	210		✓	heat
Soltis 92 F.R.	S92	S92/213	40% PL 60% PVC			267	420	0,45	4		4	13	83	4		0,51	0,06	0,28	0,04				310	210		✓	heat
Soltis 92 F.R.	S92	S92/214	40% PL 60% PVC			267	420	0,45	4		8	46	46	8		0,36	0,07	0,18	0,04				310	210		✓	heat
Soltis 92 F.R.	S92	S92/216	40% PL 60% PVC			267	420	0,45	4		5	8	87	5		0,52	0,05	0,28	0,04				310	210		✓	heat
Soltis 92 F.R.	S92	S92/221	40% PL 60% PVC			267	420	0,45	4		17	73	10	15		0,45	0,04	0,10	0,06				310	210		✓	heat
Soltis 92 F.R.	S92	S92/222	40% PL 60% PVC			267	420	0,45	4		15	63	22	10		0,29	0,11	0,15	0,05				310	210		✓	heat
Soltis 92 F.R.	S92	S92/223	40% PL 60% PVC			267	420	0,45	4		11	46	43	8		0,36	0,08	0,19	0,04				310	210		✓	heat
Soltis 92 F.R.	S92	S92/224	40% PL 60% PVC			267	420	0,45	4		5	31	64	3		0,30	0,10	0,23	0,03				310	210		✓	heat
Soltis 92 F.R.	S92	S92/225	40% PL 60% PVC			267	420	0,45	4		6	19	75	5		0,48	0,05	0,26	0,04				310	210		✓	heat

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another


Width


Composition


Health certification


IMO - Fabrics for marine industry


Solar reflection


Light absorption


Sound absorption


Thickness


Flame retardant


Colour fastness


Openess factor


Solar absorption


G tot Type C - GLASS


Warp - Weft N5 cm


Weight


Transparency


Sealable


Solar transmission


Light transmission


UV reduction


Glare control

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.

Name	Cat.	Ref.	 Composition	 F.R. classification	 Health certifications	 Width cm	 Weight g/m2	 Thickness mm	 OF %	 Shading	 TS %	 RS %	 AS %	 TL %	 RL %	 INT Type C glass	 EXT Type C glass	 INT Type D glass	 EXT Type D glass	 Glare control	↓UV %	αw	Mechanical resistance WARP daN/5cm	Mechanical resistance WEFT daN/5cm	Colour fastness to light	OUTDOOR	Sealable
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02		

Soltis 92 F.R.	S92	S92/226	40% PL 60% PVC	Euroclass B-s2,d0 (EU) Classe 1 (I), M1 (F), B1 (D), BS (GB), NFPA 701 (US), G1 (RU), VKF (CH), IMO		177	420	0,45	4		7	28	65	5		0,45	0,05	0,24	0,03				310	210		✓	heat
Soltis 92 F.R.	S92	S92/227	40% PL 60% PVC			177	420	0,45	4		2	10	88	2		0,53	0,03	0,28	0,03				310	210		✓	heat
Soltis 92 F.R.	S92	S92/228	40% PL 60% PVC			177	420	0,45	4		6	27	67	3		0,47	0,05	0,26	0,03				310	210		✓	heat
Soltis 92 F.R.	S92	S92/229	40% PL 60% PVC			177	420	0,45	4		4	17	79	3		0,51	0,04	0,28	0,03				310	210		✓	heat

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another

	Width		Composition		Health certification		IMO - Fabrics for marine industry		Solar reflection		Light absorption		Sound absorption
	Thickness		Flame retardant		Colour fastness		Openess factor		Solar absorption		G tot Type C - GLASS		Warp - Weft N5 cm
	Weight		Transparency		Sealable		Solar transmission		Light transmission		UV reduction		Glare control

MAINTENANCE HANDLE THE FABRIC WITH CARE, USING CLEAN DRY HANDS. DO NOT USE SOLVENTS OR ANY ABRASIVE SUBSTANCES THAT MAY DAMAGE THE FABRIC. WHEN CLEANING WINDOWS THE BLIND MUST BE RAISED TO AVOID ANY DIRECT OR INDIRECT SPRAY OF CLEANING PRODUCTS. REMOVE THE DUST WITH A VACUUM CLEANER OR USING COMPRESSED AIR, AVOID PULLING OR STRETCHING FABRIC. ONLY FOR PVC COATED PRODUCTS, CLEAN WITH A DAMP CLOTH OR A SPONGE DIPPED IN SOAPY WATER IF NECESSARY. RINSE WITH CLEAN WATER. DO NOT RUB. LEAVE THE BLIND DOWN UNTIL COMPLETELY DRY.