MOTTURA

Duette Classic BLO Plì 20mm

TP/3870/01

TP/3870/02

TP/3870/03

TP/3870/04

Name	Cat.	Ref.	Composition	F.R. classification	Health certifications	Width cm	Weight g/m2	Thickness mm	OF %	Shading	TS %	RS %	AS %	TL %	RL %	INT Type C glass	EXT Type C glass	INT Type D glass	EXT Type D glass	Glare control	↓UV %	αω	Mechanical resistance WARP daN/5cm	Mechanical resistance WEFT daN/5cm	Colour fastness to light	OUTDOOR	Sealable
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02		
Duette Classic BLO Plì 20mm	DO20	TP/3870/01	100% PL		OEKO-TEX	225	180	0,15		●	0	72	28	0	77	0,33					100				6/7		
Duette Classic BLO Plì 20mm	DO20	TP/3870/02	100% PL			225	180	0,15		●	0	72	28	0	77	0,33					100				6/7		
Duette Classic BLO Plì 20mm	DO20	TP/3870/03	100% PL			225	180	0,15		●	0	72	28	0	77	0,33					100				6/7		
Duette Classic BLO Plì 20mm	DO20	TP/3870/04	100% PL			225	180	0,15		●	0	72	28	0	77	0,33					100				6/7		

Tutti i coefficienti potrebbero avere una tolleranza di +/- 5%
Attenzione: La tonalità dei colori può variare leggermente da lotto a lotto

Larghezza
Composizione
Certificazione
IMO - Tessuti per settore navale
Riflessione
Riflessione luce visibile
Assorbimento acustico
Spessore
Ignifugo
Solidità luce
Fattore di apertura
Assorbimento solare
G tot Type C - GLASS
Trama - Ordito N5 cm
Peso
Trasparenza
Saldabilità
Trasmissione solare
Trasmissione luce visibile
Abbattimento UV
Glare control

MANUTENZIONE NON UTILIZZARE ACQUA: INTERVENIRE SOLO A SECCO PER RIMUOVERE DEPOSITI DI POLVERE.