



Gea Perlato F.R. Plì 20mm




TP/3800/11




TP/3800/12




TP/3800/13




TP/3800/14



TP/3800/15



TP/3800/16



Name	Cat.	Ref.																									
Reference Standard							UNI EN ISO 2286-2	UNI EN ISO 2286-3	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	UNI EN 14501	EN ISO 11654	UNI EN ISO 1421	UNI EN ISO 1421	UNI EN ISO 105 B02			

Gea Perlato F.R. Pli 20mm	GEP	TP/3800/11	100% post-consumer recycled PET	B1(D)	OEKO-TEX 	235	100	0,20			34	60	6	30	66	0,38					90				5/7		
Gea Perlato F.R. Pli 20mm	GEP	TP/3800/12		B1(D)		235	100	0,20			33	59	8	30	65	0,38					95				5/7		
Gea Perlato F.R. Pli 20mm	GEP	TP/3800/13		B1(D)		235	100	0,20			32	60	8	28	66	0,38					96				5/7		
Gea Perlato F.R. Pli 20mm	GEP	TP/3800/14		B1(D)		235	100	0,20			29	56	15	19	57	0,39					96				5/7		
Gea Perlato F.R. Pli 20mm	GEP	TP/3800/15		B1(D)		235	100	0,20			21	52	27	7	50	0,40					99				5/7		
Gea Perlato F.R. Pli 20mm	GEP	TP/3800/16		B1(D)		235	100	0,20			18	44	38	0	36	0,43					100				5/7		

All coefficients have a possible tolerance of +/- 5%
Attention: colour shades may vary slightly from one dye lot to another


Width


Composition


Health certification


IMO - Fabrics for marine industry


Solar reflection


Light absorption


Sound absorption


Thickness


Flame retardant


Colour fastness


Openess factor


Solar absorption


G tot Type C - GLASS


Warp - Weft N5 cm


Weight


Transparency


Sealable


Solar transmission


Light transmission


UV reduction


Glare control

MAINTENANCE DO NOT USE WATER: INTERVENE USING DRY METHODS FOR REMOVING DUST DEPOSITS.