



MASTER 202 F.R.




3202/02




3202/04




3202/05




3202/06




3202/66



3202/70










3202/72



3202/82



Ref.	 cm	 g/m ²						Price category	Appearance
3202/02	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/04	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/05	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/06	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/66	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/70	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/72	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain
3202/82	340	265	60% PL F.R. - 40% PL	Class 1(l)	No	Vertical ceiling/floor	Sheer	C	plain

All coefficients have a possible tolerance of +/- 5%
 Attention: colour shades may vary slightly from one dye-lot to another



Width



Flame retardant



Transparency



Leaded



Weight



Composition



Upholstery



Selvedge

MAINTENANCE

WASH IN MAX 30°, DO NOT BLEACH, DO NOT TUMBLE DRY, IRON ON LOW SETTING, CAN BE DRY CLEANED, DRIP DRY, SHRINKAGE AFTER FIRST WASH 0-2% FOR FURTHER INDICATIONS PLEASE CONSULT THE INDIVIDUAL PRODUCT SPECIFICATIONS IN THE ATELIER CATALOGUE.